

Master solutions

Your first script

```
#!/bin/bash
echo 'Hello, World!'
```

Count to 100

Make sure the parameter expansion is quoted properly. It may not be necessary here, but it is good practice.

```
#!/bin/bash
for i in {1..100}
do
    echo "$i"
done
```

Here, we use brace expansion, so we can't use quotes.

```
#!/bin/bash
echo {1..100}
```

Set up a script directory for your user

The following line should be added to either `~/.profile` or `~/.bashrc`. You have to log out and back in to make it work.

```
export PATH="$PATH:/home/user/scripts"
```

You can test whether it worked by running

```
echo "$PATH"
```

in your terminal.

Parse some options

```
#!/bin/bash
while getopts 'h?abc:' opt; do
    case "$opt" in
        h|\\?)
            echo 'Available options: -h, -a, -b, -c ARGUMENT'
            exit 0
            ;;
        a)
            echo 'Option a selected'
            ;;
        b)
            echo 'Option b selected'
            ;;
        c)
            echo "Option f selected with argument $OPTARG"
            ;;
        esac
    done
    shift $((OPTIND-1))
```

The shift line at the end is important! If you have more arguments (that aren't options), you can't access them otherwise.

Output all your arguments

```
#!/bin/bash
for i in "$@"
do
    echo "$i"
done
```

Make sure all quotes are put correctly. Especially the expression `"$@"` MUST be quoted.

Find big files

```
#!/bin/bash

usage() {
    echo "usage: $0 directory"
    exit 1
}

# We want exactly one argument
if [[ "$#" -ne 1 ]]; then
    usage
fi

dir="$1"

# Test whether argument is a directory
if ! [[ -d "$dir" ]]; then
    usage
fi

# Find files in dir, sort by size and print largest 5
find "$dir" -printf '%s %p\n' | sort -nr | head -n 5
```

The use of a function for `usage` is not required, but it's good practice.

Self-reproducing script

```
#!/bin/bash
cp "$0" backup.sh
```

This second example also works, but is bad practice: it is discouraged to use `cat` to get the contents of a file in a bash script. There are almost always better ways to do that.

```
#!/bin/bash
cat "$0" > backup.sh
```

Make your bash prompt fancy

Not much to say here, all solutions will be individual

Maze generator

`RANDOM` is an environment variable that takes on a different numeric value every time you read it.

```
#!/bin/bash
while true
do
    (( $RANDOM % 2 )) \
        && echo -n '/' \
        || echo -n '\' \
    sleep 0.07
done
```

Simple backup script

The `find` option `-type f` makes sure only files are listed (and not directories). The `-ctime -1` option makes sure only files not older than 1 day (24 hours) are listed.

```
#!/bin/bash
find . -type f -ctime -1 | xargs tar -czf 'backup.tar.gz'
```

Screen brightness control

```
#!/bin/bash

(( $# == 0 )) && {
    echo "No argument given; exiting"
    exit 1;
}

# -z tests whether string is empty (zero length). We search for + or - in the string.
if [[ -z $( echo $1 | grep -Eo "[+|-]" ) ]]
then
    newbrightness="$1"
```

```

else
    brightness="$(cat /sys/class/backlight/intel_backlight/brightness)"
    newbrightness="$(( $brightness $1 ))" # becomes for example 10 +1
fi

# prevent screen from going all black. The threshold value might vary,
# since the scale of brightness values is different on every system
if (( $newbrightness < 10 ))
then
    newbrightness=10
fi

# use tee instead of redirections because we need sudo
echo "$newbrightness" | sudo tee /sys/class/backlight/intel_backlight/brightness > /dev/null

```

The file path might of course vary. If you don't find a brightness file in `/sys/class/backlight`, chances are this script is not possible on your system.

Automatic update script

This script is designed to be used with `sudo`, i.e. `sudo updatescript`. If you use it like that, you don't need `sudo` for zypper inside the script.

```

#!/bin/bash
# First, move old files out of the way safely. Discard error messages.
mv -b /home/user/updatescript /home/user/updatescript-old > /dev/null 2>&1

{ zypper up > /home/user/updatescript } \
    && rm /home/user/updatescript

poweroff

```

Of course, the zypper command is for openSUSE, and other distros require other commands.

Disable/Enable external monitor output

These are some examples. It depends on your setup what you need.

```

#!/bin/bash
xrandr --output HDMI-0 --auto --left-of LVDS-0

```

```

#!/bin/bash
xrandr --output HDMI-0 --auto
xrandr --output LVDS-0 --off

```

```

#!/bin/bash
# detect a monitor
if xrandr | grep 'HDMI-0 connected' > /dev/null
then
    xrandr --output HDMI-0 --right-of LVDS-0
fi

```

Display a random headline from Reddit

This exercise requires you to parse strings to display them nicely. That can be quite tedious, and the commands used for it are often cryptic (cf. `sed`). Don't be scared.

```

#!/bin/bash
curl -A 'Mozilla/5.0 (Windows; U; MSIE 7.0; Windows NT 6.0; en-US)' -s
    https://www.reddit.com/r/showerthoughts.json \
    | jq -r '.data[0].title' \
    | shuf -n 1 \
    | sed 's/\\//g' \
    | sed 's/^"/' \
    | sed 's/"$//'

```

The three `sed`s are merely for pretty printing. The first removes backslashes, the second removes the first quote and the last removes the last quote.

In a `sed` expression, `^` matches the beginning of a line and `$` matches the end. Also, backslashes (among other characters) have to be *escaped* using yet another backslash.

Wallpaper change every 10 minutes

You can run this script in the background, like this: `./wallpaperscript &`

```
#!/bin/bash
while true
do
    feh --bg-fill --randomize ~/pictures/wallpaper/*
    sleep $(( 60 * 10 ))
done
```

Your own TODO program

```
#!/bin/bash
# use a subshell to contain the directory change
(
    # we work in .config, this isn't mandatory. ~/.config is where many
    # programs store user configuration.
    mkdir -p ~/.config/todo
    cd ~/.config/todo
    touch todolist # touch creates a file if it doesn't exist yet

    while getopts 'i:d:h' opt; do
        case "$opt" in
            h|\?)
                echo 'Valid flags: -i -d -h'
                ;;
            i)
                echo "$OPTARG" >> todolist
                ;;
            d)
                # sed '3d' deletes the 3rd line from a file.
                sed -e "${OPTARG}d" todolist > /tmp/todolist
                cp /tmp/todolist todolist
                ;;
            esac
        done
        # the -n option adds line numbers
        cat -n todolist
    )
```

Reminder script

```
#!/bin/bash
mins="$1"
shift 1

echo notify-send "'$@" | at now + "$mins" min &>/dev/null
echo "Reminder: $@ set for $mins mins from now."
```

Youtube downloader

```
#!/bin/bash

query="$@"

# get youtube search results page
# search for links that contain 'watch?v=' followed by 11 characters
# take the first one
ytid=$( \
    curl -s --data-urlencode "search_query=$query" https://www.youtube.com/results \
    | grep -oE 'watch?v={11}' \
    | head -n 1 \
)

echo "$ytid"

youtube-dl -f bestaudio -o "%(title)s_%(id)s.%(ext)s" "https://www.youtube.com/$ytid"
```

Web radio

```
#!/bin/bash

# tidy up first
killall mpv

# The & is not required but useful. Cache size is increased for lag free streaming
mpv http://213.251.190.165:9000 -cache 1024 &
```

Image resizer

```
#!/bin/bash

mkdir -p resized

for i in *
do
    # The > indicates that ImageMagick should only shrink larger images
    convert "$i" -resize '100x100>' resized/"$i"
done
```

Assignment-fetcher

```
#!/bin/bash

while getopts 'h?lf:u:p:' opt; do
    case "$opt" in
        h|\?)
            echo "usage: $0 [-l] [-f FILTER] [-u USER] [-p PASSWORD] URL"
            exit 0
            ;;
        f)
            filter="$OPTARG"
            ;;
        u)
            user="$OPTARG"
            ;;
        p)
            pass="$OPTARG"
            ;;
        l)
            list=true
            ;;
    esac
done

shift $((OPTIND-1))

url=$1

# Bare url up to the first slash.
# The grep first finds all characters up to the first dot, and then from there on finds
# all characters that are NOT slashes up to the first slash.
# The sed is used to escape all slashes within the url. / becomes \/
baseurl=$( \
    echo $url \
    | grep -oe '.*\.[^/]*/' \
    | sed -e 's/\//\\/g' \
)

# URL without file name (up to the last slash).
# The grep just finds everything up to a slash. By default it uses greedy matching,
# which means that it finds the longest fitting sequence.
# The sed is used to escape all slashes within the url.
longurl=$( \
    echo $url \
    | grep -oe '.*/' \
    | sed -e 's/\//\\/g' \
)

# The last command used in the command chain below depends on an option.
# if -l was passed, we just echo the found pdfs. Otherwise download them.
if [ $list == true ]
then
    # the -n option is for xargs
    lastcmd="-n 1 echo"
else
    lastcmd="wget --user $user --password $pass"
fi

# First, find strings that end in .pdf
# Then, prepend the base url to all strings that are relative urls
# Then, apply the filter
# Then, if an url starts with // (relative to root), prepend the longurl
# last, download or display the urls
curl -s $url \
    | grep -oe '[^"]*\.[pdf]' \
    | sed -e "s/^\//$baseurl/" \
    | grep -e "/[^"]*$filter[^"]*\.[pdf]" \
    | awk '{ if ( $0 !~ /\// ) { print "\"$longurl\" \"$0\" } else {print} }' 2>/dev/null \
    | xargs $lastcmd
```